

01/10/2021

PRICE NET

**POLYCARBONATE EXTRUDED TUBES PRICE LIST**

DIAMETRO Mm	SPESS. MM	PREZZO al MI	DIAMETRO Mm	SPESS. MM	PREZZO al MI	DIAMETRO Mm	SPESS. MM	PREZZO al MI
10//7	1,5	2,16 €	40/36	2	5,18 €	110/104	3	22,62 €
12//9	1,5	2,35 €	40/37	1,5	4,31 €	110/105	2,5	19,21 €
12//10	1	1,77 €	40/38	1	3,39 €	110/106	2	15,98 €
13//9	2	2,48 €	45/42	1,5	5,40 €	120/110	5	37,51 €
15//10	2,5	2,73 €	50/44	3	10,50 €	120/112	4	30,32 €
15//11	2	2,42 €	50/45	2,5	8,93 €	120/114	3	22,92 €
16//12	2	2,52 €	50/46	2	7,53 €	130/120	5	40,60 €
18/14	2	2,79 €	50/47	1,5	5,99 €	130/122	4	32,76 €
20/14	3	4,22 €	60/54	3	12,01 €	130/124	3	25,14 €
20/16	2	3,08 €	60/55	2,5	10,16 €	134/124	5	42,64 €
24/20	2	3,49 €	60/56	2	8,38 €	134/126	4	34,14 €
25/21	2	3,69 €	70/64	3	14,69 €	134/128	3	25,83 €
25/22	1,5	2,79 €	70/65	2,5	12,20 €	150/140	5	47,57 €
30/24	3	6,26 €	70/66	2	10,50 €	150/142	4	37,91 €
30/25	2,5	5,40 €	75/69	3	15,34 €	150/144	3	30,81 €
30/26	2	4,34 €	80/74	3	16,35 €	180/170	5	56,22 €
30/27	1,5	3,69 €	80/75	2,5	14,09 €	180/172	4	45,38 €
30/28	1	3,08 €	80/76	2	11,87 €	180/174	3	34,69 €
32/26	3	6,75 €	90/84	3	18,52 €	200/190	5	62,70 €
36/30	3	7,53 €	90/85	2,5	15,58 €	200/192	4	49,28 €
36/32	2	5,26 €	90/86	2	12,94 €	200/194	3	39,14 €
38/34	2	5,53 €	100/94	3	20,68 €	250/240	5	80,27 €
38/35	1,5	4,14 €	100/95	2,5	17,19 €	250/242	4	63,72 €
40/34	3	7,58 €	100/96	2	14,23 €	250/244	3	48,33 €

**FROM Ø 10 UP TO Ø 20 = FROM PACKAGE 10 PIECES**

**FROM Ø 24 UP TO Ø 36 = FROM PACKAGE 5 PIECES**

**FROM Ø 38 UP TO Ø 250 = FROM PACKAGE 1 PIECE**

**STANDARD LENGHTS =** UP TO THE EXTERNAL Ø 40 mm 2000 mm, OVER 40 mm 2050

**TOLERANCES ON THE EXTERNAL Ø** = from Ø 10 mm up to Ø 150 +/- 1%, from Ø 160 mm up to Ø 250 mm +/-

**TOLERANCES ON THE INTERNAL Ø** = from Ø 10 mm up to Ø 150 +/- 1,5%, from Ø 160 mm up to Ø 250 mm +/-

**TOLERANCES ON WALL THICKNESS** = from Ø 10 mm up to Ø 64 +/- 5%, from Ø 70 mm up to Ø 100 mm +/- 8%  
 from Ø 110 mm up to Ø 200 mm +/- 10%, from Ø 220 mm. Up to Ø 250 +/-

**LENGHTS TOLERANCES** = +/- 1 mm

**FORMULA FOR THE CALCULATION OF THE MAXIMUM INTERNAL ALLOWABLE PRESSURE**

internal pressure of the tube in atmospheres or bar ( 1bar=0,1N/mm)=

100x thickness of the tube in mm :external diameter of the tube in mm

this formula is valid for standard test conditions and it means with 20°C room temperature and 50% of relative hum



.it

2%  
- 2,5%  
%  
- 15%

idity